

HANA Injectors Comparison Chart

Current type/color	Previous type/color	Nozzle/index	Coil resistance	MAX Power (HP)				note
				HP/cylinder (+/- 15 %)	x 4 cyl	x 6 cyl	x 8 cyl	
Type A + (blue)	Type A + (blue)	without	1,3 Ohm	40 / 50 / 60 HP	160 ~ 240 HP	240 ~ 360 HP	320 ~ 480 HP	pressure 0.8/1.0/1.2 bar (with max.load)
Type A (gold)	Type A (green)	without	1,9 Ohm	33 / 42 / 50 HP	132 ~ 200 HP	198 ~ 300 HP	264 ~ 400 HP	pressure 0.8/1.0/1.2 bar (with max.load)
Type B (gold)	Type B (red)	2,4 mm (one stripe)	1,9 Ohm	26 / 32 / 39 HP	104 ~ 156 HP	156 ~ 234 HP	208 ~ 312 HP	pressure 0.8/1.0/1.2 bar (with max.load)
Type C (gold)	Type C (black)	2,1 mm (two stripes)	1,9 Ohm	20 / 25 / 30 HP	80 ~ 120 HP	120 ~ 180 HP	160 ~ 240 HP	pressure 0.8/1.0/1.2 bar (with max.load)
Type D (gold)	Type D (violet)	1,9 mm (three stripes)	1,9 Ohm	15 / 19 / 24 HP	60 ~ 96 HP	90 ~ 144 HP	120 ~ 192 HP	pressure 0.8/1.0/1.2 bar (with max.load)

www.lpgshop.co.uk